MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0547 4" X 36" BELT/6" DISC COMBO SANDER

Product Dimensions:

Weight	34 lbs.
Width (side-to-side) x Depth (front-to-back) x Height	17-1/2 x 14-3/8 x 23-3/4 in.
Footprint (Length x Width)	14-5/8 x 6-5/8 in.

Shipping Dimensions:

Type	Cardboard Box
Content	Machine
Weight	39 lbs.
Length x Width x Height	12 x 22 x 11 in.

Electrical:

Power Requirement	110V, Single-Phase, 60 Hz
Prewired Voltage	110V
Full-Load Current Rating	5A
Minimum Circuit Size	15A
Connection Type	Cord & Plug
Power Cord Included	Yes
Power Cord Length	4 ft.
Power Cord Gauge	18 AWG
Plug Included	Yes
Included Plug Type	5-15
Switch Type	Toggle Safety Switch w/Removable Key

Motors:

Main

Horsepower	1/3 HP
Phase	Single-Phase
Amps	5A
Speed	3450 RPM
Type	ODP Permanent-Split Capacitor
Power Transfer	Belt Drive
Bearings	Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type	N/A

Main Specifications:

Belt Sander Info

Sanding Belt Width	4 in.
Sanding Belt Length	36 in.
Sanding Belt Speed	1970 FPM
Sanding Belt Tilt	90 deg.
Max Height of Belt in Vertical Position	23-3/4 in.
Belt Tension Release Type	Quick Release
Platen Type	Steel
Platen Length	12-1/4 in.
Platen Width	4-3/8 in.

The information contained herein is deemed accurate as of 4/17/2024 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.

Disc Sander Info

Disc Diameter	6 in.
Disc Speed	3450 RPM
Disc Sandpaper Backing Type	PSA
Table Length	6-1/4 in.
Table Width	8-7/8 in.
Table Tilt	Left 0, Right 45 deg.
Table-to-Floor Height	4-3/4 in.

Construction Materials

Base	Cast Iron
Table	Die-Cast Aluminum
Frame	Cast Iron
Disc	Aluminum
Miter Gauge	Plastic/Steel Bar
Paint Type/Finish	Powder Coated

Other Related Info

Miter Gauge Slot Width	5/8 in.
Miter Gauge Slot Height	1/4 in.
Number of Dust Ports	1
Dust Port Size	2-1/2 in.

Other Specifications:

Country of Origin	China
Warranty	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label
ISO 9001 Factory	No
Certified by a Nationally Recognized Testing Laboratory (NRTL)	No

Features:

Adjustable Miter Gauge
Single Knob Tracking Adjustment
Built In Dust Port
Cast-Iron Construction