



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0555 THE ULTIMATE 14" BANDSAW

### Product Dimensions:

Weight..... 167 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 28 x 30-1/4 x 66-1/2 in.  
Footprint (Length x Width)..... 24-1/2 x 17-1/2 in.

### Shipping Dimensions:

Type..... Cardboard  
Content..... Machine  
Weight..... 198 lbs.  
Length x Width x Height..... 44 x 21 x 20 in.

### Electrical:

Power Requirement..... 110V/220V, Single-Phase, 60 Hz  
Prewired Voltage..... 110V  
Minimum Circuit Size..... 15A at 110V, 15A at 220V  
Switch..... On/Off Push Button w/Disabling Padlock  
Switch Voltage..... 110V/220V  
Cord Length..... 6 ft.  
Cord Gauge..... 16 Gauge  
Plug Included..... Yes  
Included Plug Type..... NEMA 5-15 for 110V  
Recommended Plug/Outlet Type..... NEMA 6-15 for 220V

### Motors:

#### Main

Type..... TEFC Capacitor Start Induction  
Horsepower..... 1 HP  
Voltage..... 110V/220V  
Prewired..... 110V  
Phase..... Single  
Amps..... 11A at 110V, 5.5A at 220V  
Speed..... 1725 RPM  
Cycle..... 60 Hz  
Number of Speeds..... 1  
Power Transfer ..... Belt Drive  
Bearings..... Shielded and Lubricated

### Main Specifications:

#### Operation

Bandsaw Size..... 14 in.  
Blade Speeds..... 1500, 3200 FPM  
Table Tilt..... Left 15, Right 45 deg.

#### Cutting Capacities

Maximum Cutting Height..... 6 in.  
Max Capacity Left of Blade..... 13-1/2 in.

**Blade Information**

Standard Blade Length..... 93-1/2 in.  
Blade Length Range..... 92-1/2 - 93-1/2 in.  
Blade Width Range..... 1/8 - 3/4 in.  
Upper Blade Guides..... Ball Bearing  
Lower Blade Guides..... Ball Bearing  
Guide Post Size..... 0.865 in. (22mm)  
Guide Post Type..... Solid Steel

**Table Information**

Table Length..... 14 in.  
Table Width..... 14 in.  
Table Thickness..... 1-1/2 in.  
Floor to Table Height..... 43-5/16 in.

**Fence Information**

Locks in Front..... Yes  
Locks in Rear..... No  
Adjustable for Blade Lead..... Yes

**Construction**

Table..... Precision Ground Cast Iron  
Rip Fence ..... Deluxe Extruded Aluminum  
Base..... Pre-Formed Steel  
Body..... Cast Iron  
Upper Wheel..... Computer Balanced Cast Aluminum  
Lower Wheel..... Computer Balanced Cast Aluminum  
Tire..... Rubber  
Wheel Cover ..... Pre-Formed Steel  
Paint..... Powder Coated

**Other Related Information**

Wheel Diameter..... 13-3/4 in.  
Wheel Width..... 1-3/16 in.  
Number of Dust Ports..... 1  
Dust Port Size..... 4 in.  
Mobile Base..... G7314Z

**Other Specifications:**

ISO Factory ..... ISO 9001  
Country Of Origin ..... Taiwan  
Warranty ..... 1 Year  
Serial Number Location ..... Name Label on Top Cover  
Awards ..... Popular Woodworking Best New Tool 2003  
Assembly Time ..... 1 Hours

**Features:**

- Includes Fence and Miter Gauge
- Upper and Lower Ball Bearing Blade Guides
- Deluxe Heavy-Duty Stand
- Magnifying Window Over Fence Scale
- Hinged Wheel Covers
- 4" Dust Port
- 6" Riser Block Available
- Powder Coated Paint