



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0568 24" 5 HP INDUSTRIAL BANDSAW

Product Dimensions:

Weight..... 836 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 48 x 32 x 83-1/2 in.
Footprint (Length x Width)..... 41-3/8 x 23-1/2 in.

Shipping Dimensions:

Type..... Wood Slat Crate
Content..... Machine
Weight..... 951 lbs.
Length x Width x Height..... 27 x 45 x 87 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Full-Load Current Rating..... 23A
Minimum Circuit Size..... 30A
Power Cord Included..... Yes
Power Cord Length..... 80 in.
Power Cord Gauge..... 12 AWG
Plug Included..... Yes
Included Plug Type..... L6-30
Switch Type..... Control Panel w/Magnetic Switch Protection & Lockout Key

Motors:

Main

Horsepower..... 5 HP
Phase..... Single-Phase
Amps..... 23A
Speed..... 1720 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer V-Belt Drive
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Main Specifications

Bandsaw Size..... 24 in.
Max Cutting Width (Left of Blade)..... 24-1/2 in.
Max Cutting Width (Left of Blade) w/Fence..... 23-1/4 in.
Max Cutting Height (Resaw Height)..... 16-1/4 in.
Blade Speeds..... 5300 FPM

Blade Information

Standard Blade Length..... 181 in.
Blade Length Range..... 180 – 181-1/2 in.
Blade Width Range..... 1/4 – 1-1/2 in.
Type of Blade Guides..... Double Ball Bearing
Guide Post Adjustment Type..... Rack & Pinion
Has Quick-Release..... Yes

Table Information

Table Length.....	23-5/8 in.
Table Width.....	33-1/2 in.
Table Thickness.....	2 in.
Table Tilt.....	Right 45 deg.
Table Tilt Adjustment Type.....	Rack & Pinion
Floor-to-Table Height.....	34-1/2 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	No
Resaw Fence Attachment Included.....	No
Miter Gauge Included.....	Yes

Miter Gauge Information

Miter Angle.....	0 - 60 deg. L/R
Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Width.....	3/4 in.
Miter Gauge Slot Height.....	3/8 in.

Construction Materials

Table.....	Precision Ground Cast Iron
Trunnion.....	Cast Iron
Fence.....	Precision Ground Cast Iron
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Pre-Formed Steel
Wheels.....	Computer-Balanced Cast Iron
Tire.....	Rubber
Wheel Cover	Pre-Formed Steel
Paint Type/Finish.....	Powder Coated

Other Related Information

Wheel Diameter.....	24-3/4 in.
Wheel Width.....	1-3/4 in.
Number of Dust Ports.....	2
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D2058A, D2246A

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	60 Minutes
Serial Number Location	ID Label
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	No

Features:

- Ball Bearing Blade Guides
- Green and Putty Powder-Coat Paint
- Blade Tension Indicator
- Blade Tracking Window
- Quick Change Blade Release/Tensioning
- Round Fence Rail
- Two 4" Dust Ports
- Hinged Wheel Covers
- Micro-Adjusting Rack & Pinion Table Tilt
- Height Scale Measurement
- Includes 1" Blade
- Included Miter Gauge
- Computer Balanced Cast-Iron Wheels
- Rack and Pinion Upper Guide Adjustment
- Foot Brake Stop