



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0656W 8" X 72" JOINTER WITH MOBILE BASE

Product Dimensions:

Weight..... 434 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 73 x 32 x 46-1/2 in.
Footprint (Length x Width)..... 30 x 17-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Wood Crate
Content..... Machine
Weight..... 379 lbs.
Length x Width x Height..... 81 x 23 x 15 in.
Must Ship Upright..... Yes

Carton #2

Type..... Cardboard Box
Content..... Stand
Weight..... 139 lbs.
Length x Width x Height..... 28 x 20 x 27 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 240V, Single-Phase, 60 Hz
Prewired Voltage..... 240V
Full-Load Current Rating..... 12A
Minimum Circuit Size..... 20A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 12 AWG
Plug Included..... Yes
Included Plug Type..... 6-20
Switch Type..... ON/OFF Push Button Switch w/Large Shut-Off Paddle

Motors:

Main

Horsepower..... 3 HP
Phase..... Single-Phase
Amps..... 12A
Speed..... 3450 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Main Specifications

Jointer Size.....	8 in.
Bevel Jointing.....	0 – 45 deg. L/R
Maximum Width of Cut.....	8 in.
Maximum Depth of Cut.....	1/8 in.
Minimum Workpiece Length.....	8 in.
Minimum Workpiece Thickness.....	1/2 in.
Maximum Rabbeting Depth.....	1/2 in.
Number of Cuts Per Minute.....	21,400

Fence Information

Fence Length.....	35 in.
Fence Width.....	1-1/2 in.
Fence Height.....	5 in.
Fence Stops.....	45, 90, 135 deg.

Cutterhead Information

Cutterhead Type.....	4 Knife
Cutterhead Diameter.....	3 in.
Cutterhead Speed.....	5350 RPM

Knife Information

Number of Knives.....	4
Knife Type.....	HSS, Single-Sided
Knife Length.....	8-1/16 in.
Knife Width.....	3/4 in.
Knife Thickness.....	1/8 in.
Knife Adjustment.....	Jack Screws

Table Information

Table Length.....	73 in.
Table Width.....	9-3/8 in.
Table Thickness.....	2 in.
Floor to Table Height.....	32-1/4 in.
Table Adjustment Type.....	Handwheel
Table Movement Type.....	Dovetailed Ways

Construction

Base.....	Cast Iron
Body Assembly.....	Cast Iron
Cabinet.....	Pre-formed Steel
Fence Assembly.....	Cast Iron
Guard.....	Die Cast Metal
Table.....	Precision-Ground Cast Iron
Paint Type/Finish.....	Powder Coated

Other Information

Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Mobile Base.....	Built-In

Other Specifications:

Country of Origin	China
Warranty	1 Year
Approximate Assembly & Setup Time	1 Hour
Serial Number Location	ID Label
ISO 9001 Factory	No
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features:

- Beds Slide on Dovetailed Ways
- Handwheel Adjusted Tables with Depth Gauge
- Pedestal-Mounted Switch for Easy Access
- Center-Mounted Fence with Rack and Pinion Adjustment
- Fence Stops at 45, 90, and 135 Degrees
- Poly-V Serpentine Belt Drive System for Vibration Reduction and Quieter Operation
- Pair of Push Blocks Included
- 4" Dust Port with Built-In Dust Chute
- 4-Knife Cutterhead
- Precision-Ground Cast-Iron Tables
- Green and Putty Powder Coated Paint
- Sturdy Cabinet Stand with Built-in Mobile Base
- Included Knife Setting Jig
- Rabbeting Table
- Super Long 73-1/2" Bed

Accessories Included:

- Open-End Wrenches 8/10, 11/13mm
- Hex Wrenches 3, 4, 5, 6, 8mm
- Torx Wrench T20 x 150
- Torx Wrench T20 x 75
- Push Blocks