



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0803Z 9" BENCHTOP BANDSAW W/ LASER GUIDE & QUICK RELEASE

Product Dimensions:

Weight..... 42 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 21 x 17 x 30 in.
Footprint (Length x Width)..... 16 x 6-1/2 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 49 lbs.
Length x Width x Height..... 32 x 18 x 14 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 2.8A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 80 in.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1/3 HP
Phase..... Single-Phase
Amps..... 2.8A
Speed..... 1725 RPM
Type..... ODP Induction
Power Transfer Belt

Main Specifications:

Main Specifications

Bandsaw Size..... 9 in.
Max Cutting Width (Left of Blade)..... 9 in.
Max Cutting Width (Left of Blade) w/Fence..... 4-1/2 in.
Max Cutting Height (Resaw Height)..... 3-5/8 in.
Blade Speeds..... 2460 FPM

Blade Information

Standard Blade Length.....	62 in.
Blade Length Range.....	61-13/16 - 62-3/16 in.
Blade Width Range.....	1/8 - 3/8 in.
Type of Blade Guides.....	Ball Bearing
Guide Post Adjustment Type.....	Rack & Pinion
Has Quick-Release.....	Yes

Table Information

Table Length.....	11-3/4 in.
Table Width.....	11-3/4 in.
Table Thickness.....	5/8 in.
Table Tilt.....	0 - 45 deg.
Table Tilt Adjustment Type.....	Rack & Pinion
Floor-to-Table Height.....	13 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	Yes
Miter Gauge Included.....	Yes

Miter Gauge Information

Miter Angle.....	0 - 60 deg. L/R
Miter Gauge Slot Type.....	Straight Slot
Miter Gauge Slot Width.....	5/8 in.
Miter Gauge Slot Height.....	1/4 in.

Construction Materials

Table.....	Cast Aluminum
Trunnion.....	Cast Aluminum
Fence.....	Extruded Aluminum
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Pre-Formed Steel
Wheels.....	Balanced Aluminum
Tire.....	Rubber
Wheel Cover	Steel
Paint Type/Finish.....	Urethane

Other Related Information

Wheel Diameter.....	9-5/16 in.
Wheel Width.....	5/8 in.
Number of Dust Ports.....	1
Dust Port Size.....	2 in.
Has Work Light.....	Yes
Light Socket Type.....	3V LED
Maximum Bulb Wattage.....	0.5W
Has Laser Guide.....	Yes
Laser Classification.....	Class II
Laser Wavelength.....	650nm
Laser Maximum Output.....	5mW

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features:

- Class II Laser Sight
- Adjustable Wheels for Alignment/Coplanarity
- Fence Adjustable for Blade Lead
- Rack & Pinion Table Tilt
- Ball-Bearing Blade Guides
- Quick-Release Blade Tension Lever
- Extruded Aluminum Rip Fence with Camlock Handle
- Lower Wheel Brush to Prevent Build-Up of Dust/Pitch on Wheel
- 2" Dust Port
- Dust Blower
- LED Work Light

Accessories Included:

- Push Stick
- Miter Gauge