



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1014ZX COMBINATION SANDER WITH CABINET STAND

Product Dimensions:

Weight..... 148 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 30 x 24 x 56 in.
Footprint (Length x Width)..... 15 x 16-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard
Content..... Machine
Weight..... 104 lbs.
Length x Width x Height..... 19 x 28 x 15 in.

Carton #2

Type..... Cardboard
Content..... Stand
Weight..... 52 lbs.
Length x Width x Height..... 20 x 17 x 28 in.

Electrical:

Minimum Circuit Size..... 20 amp
Switch..... Safety Key Type
Switch Voltage..... 110V
Cord Length..... 8-1/2 ft.
Cord Gauge..... 16 gauge
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3/4 HP
Voltage..... 110/220V
Prewired..... 110V
Phase..... Single
Amps..... 12/6A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Sealed, Permanently Lubricated

Main Specifications:

Table Info

Table Tilt.....	0 - 45 deg.
Floor To Table Height.....	37-1/2 in.
Miter Gauge Slot Width.....	3/4 in.
Miter Gauge Slot Height.....	13/32 in.
Disc Table Length.....	12-1/4 in.
Disc Table Width.....	6 in.
Disc Table Thickness.....	1 in.

Belt Info

Sanding Belt Width.....	6 in.
Sanding Belt Length.....	48 in.
Sanding Belt Speed.....	2300 FPM
Belt Arm Tilt.....	0 - 90 deg.
Height Belt Arm Horizontal.....	42 in.
Height Belt Arm Vertical.....	58 in.
Belt Release.....	Quick Release
Drive Roller Type.....	Aluminum
Drive Roller Length.....	6 in.
Drive Wheel Diameter.....	3-1/2 in.
Idler Roller Type.....	Aluminum
Idler Roller Length.....	6 in.
Idler Roller Diameter.....	3-1/2 in.

Spindle Info

Arbor Size.....	5/8 in.
Total Arbor Length.....	11-1/2 in.

Disc Info

Sanding Disc Diameter.....	9 in.
Sanding Disc Speed.....	3450 RPM

Platen Info

Platen Type.....	Graphite Coated
Platen Length.....	17 in.
Platen Width.....	6-1/4 in.
Platen Travel.....	0 - 90 deg.

Construction

Base.....	Cast Iron
Stand.....	Sheet Metal
Table.....	Cast Iron
Frame.....	Cast Iron
Disc.....	Cast Iron
Miter Gauge.....	Die Cast Aluminum
Paint.....	Powder Coated

Other

No. Of Dust Ports.....	2
Dust Port Size.....	2, 2-1/2 in.
Mobile Base.....	G8683Z

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	On the Stand
Assembly Time	30 minutes

Features:

Solid Cabinet Stand
Built-in Storage Shelf
Quick Belt Release Mechanism
Cast Iron Table, Disc and Body