



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL H2936 28" X 39" DOWNDRAFT TABLE

Product Dimensions:

Weight..... 209 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 39-3/8 x 28 x 39-3/8 in.
Footprint (Length x Width)..... 28 x 39-3/8 in.

Shipping Dimensions:

Type..... Cardboard/Wood Runner
Content..... Machine
Weight..... 252 lbs.
Length x Width x Height..... 30 x 41 x 36 in.

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 8.5A
Minimum Circuit Size..... 15A
Switch..... Grizzly Toggle with Lockout Key
Switch Voltage..... 120V
Cord Length..... 12 ft.
Plug Included..... Yes
Included Plug Type..... NEMA 5-15

Motors:

Main

Type..... Open
Horsepower..... 1/2 HP
Voltage..... 120V
Phase..... Single
Amps..... 8.5A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Operation Info

Air Suction Cap..... 1300 CFM
First Stage Filter Micron..... 1
Second Stage Filter Micron..... 0.3
Filter Efficiency..... 25-30 Percent ASHRAE 52.1
Impeller Type..... Squirrel Cage
Impeller Size..... 9-1/2 in.

Filter Info

No. Of First Stage Filters.....	1
First Stage Filter Length.....	25 in.
First Stage Filter Width.....	16 in.
First Stage Filter Thickness.....	1 in.
No. Of Second Stage Filters.....	1
Second Stage Filter Length.....	25 in.
Second Stage Filter Width.....	16 in.
Second Stage Filter Thickness.....	2 in.

Table Info

Table Size Length.....	37 in.
Table Size Width.....	28 in.
Floor To Table Height.....	32 in.
No. Of Table Inserts.....	110
Table Insert Diameter.....	1-3/8 in.

Construction Info

Frame.....	Pre-Formed Steel
Base.....	Pre-Formed Steel on Casters
Impeller.....	Heavy-Duty Plastic
Table.....	Sheet Metal
Side Wall.....	Steel
Filter.....	Woven Fabric
Table Inserts.....	Rubber
Paint.....	Powder Coated

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	ID Label
Assembly Time	20 minutes

Features:

- Non-Marring Rubber Support Grommets
- Easy Access Filter Bay
- Quiet Operation
- Power Cord Hanger
- Two 120V Outlets for Handheld Sanders